



HAL
open science

Analyse Relationnelle de Concepts

Marianne Huchard

► **To cite this version:**

Marianne Huchard. Analyse Relationnelle de Concepts. Journée Charles Hermite "Gestion de la connaissance à l'aide des méthodes formelles", Dec 2014, Nancy, France. lirmm-01154430

HAL Id: lirmm-01154430

<https://hal-lirmm.ccsd.cnrs.fr/lirmm-01154430v1>

Submitted on 21 May 2015

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Relational Concept Analysis (RCA)

*Journée Charles Hermite
Gestion de la connaissance à l'aide des méthodes formelles*

Introduction to RCA by Marianne Huchard

Followed by Tool presentation by Xavier Dolques

Nancy, 10 décembre 2014

Brief presentation of FCA – Formal Concept Analysis

A methodology for:






- ▶ data analysis, data mining
- ▶ knowledge representation
- ▶ unsupervised learning

Roots:

- ▶ lattice theory, Galois connections (Birkhoff, 1940; Barbut & Monjardet, 1970)
- ▶ concept lattices (Wille, 1982)


Brief presentation of FCA – Formal Concept Analysis

- ▶ Handled data
 - ▶ entities (objects) with characteristics (attributes)
 - ▶ provided with a Formal Context (a binary table)

	flying	nocturnal	feathered	migratory	with_crest	with_membrane
 flying squirrel	×					×
 bat	×	×				×
 ostrich			×			
 flamingo	×		×	×		
 chicken	×		×		×	

- ▶ Concept : maximal group of entities sharing characteristics
- ▶ Concept lattice : concepts with a partial order relation


Brief presentation of FCA – Formal Concept Analysis




FCA and complex data

- ▶ many-valued contexts (integers, floats, terms, structures, symbolic objects, intervals, etc.)
(Ganter/Wille, Polaillon, ...)
- ▶ fuzzy descriptions (Yahia et al., Belohlavek, ...)
- ▶ hierarchies on values (Godin et al., Carpineto/Romano, ...)
- ▶ logical description (Chaudron et al., Ferré et al., ...)
- ▶ pattern structures (Kuznetsov, ...)
- ▶ graphs (Liquière, Prediger/Wille, Ganter/Kuznetsov, ...)
- ▶ **multi-relational data** (Priss, Hacène-Rouane et al., ...)


A flavor of Relational Concept Analysis




A flavor of Relational Concept Analysis




A flavor of Relational Concept Analysis




A flavor of Relational Concept Analysis




A flavor of Relational Concept Analysis



A flavor of Relational Concept Analysis



has-topping



Relational Concept Analysis (RCA)

- ▶ Extends the purpose of FCA for taking into account object categories and links between objects
- ▶ Main principles:
 - ▶ a relational model based on the entity-relationship model
 - ▶ integrate relations between objects as *relational* attributes
 - ▶ iterative process
- ▶ RCA provides a set of interconnected lattices

Joint formalization work with:

A. Napoli, C. Roume, M. Rouane-Hacène, P. Valtchev

M. Rouane Hacene, M. Huchard, A. Napoli, P. Valtchev. Relational concept analysis: mining concept lattices from multi-relational data, Ann. Math. Artif. Intell. 67(1), pp. 81-108, 2013

Relational Context Family (RCF)

Relational Context Family

A simple populated Entity-Relationship model

- ▶ **object-attribute contexts**
 - ▶ Pizza
 - ▶ Ingredient
- ▶ **object-object context**
 - ▶ $\text{has-topping} \subseteq \text{Pizza} \times \text{Ingredient}$

RCF / object-attributes contexts

Pizza	thin	thick	calzone
okonomi			×
alberginia		×	
margherita	×		
languedoc	×		
four-cheeses	×		
three-cheeses	×		
frutti-di-mare	×		
quebec		×	
regina	×		
hawai		×	
lorraine	×		
kebab			×

Ingredient	fruit-vege.	meat	fish	dairy	cereal-legum.	veg-oil
tomato-sauce	×					
cream				×		
tomato	×					
basilic	×					
olive	×					
olive oil						×
soy	×					
mushroom	×					
eggplant	×					
onion	×					
pepper	×					
ananas	×					
mozza				×		
goat-cheese				×		
emmental				×		
fourme-ambert				×		
squid			×			
shrimp			×			
mussels			×			
ham		×				
bacon		×				
chicken		×				
maple-sirup	×					
corn						

RCF / object-object context / part 1

has-topping	tomato-sauce	cream	tomato	basilic	olive	olive oil	soy	mushroom	eggplant	onion	pepper	ananas
okonomi	x					x	x	x				
alberginia	x					x	x		x	x		
margherita	x		x	x	x	x						
languedoc	x		x	x	x	x				x	x	
four-cheeses		x										
three-cheeses		x										
frutti-di-mare	x				x	x						
quebec	x											
regina	x							x				
hawai	x											x
lorraine		x								x		
kebab	x		x		x					x		

RCF / object-object context / part 2

	mozza	goat-cheese	emmental	fourme-ambert	squid	shrimp	mussels	ham	bacon	chicken	maple-sirup	corn
has-topping												
ekonomi												
alberginia												
margherita	x											
languedoc	x											
four-cheeses	x	x	x	x								
three-cheeses	x	x	x									
frutti-di-mare	x				x	x	x					
quebec	x							x			x	x
regina	x								x			
hawai	x							x				
lorraine			x						x			
kebab			x							x		


Data patterns we would like to extract

Using a classification on ingredients by their categories of topping (fruit-vegetable, dairy, etc.)

- ▶ create groups and classifications
 - ▶ The group of pizzas that contain at least one topping which is a vegetable
 - ▶ The group of pizzas (four-cheese and three-cheese) that have all their topping in dairy ingredients
- ▶ find implications
 - ▶ For pizzas: have meat \Rightarrow have dairy
 - ▶ For pizzas: being thin \Rightarrow have at least dairy
 - ▶ For pizzas: have only dairy \Rightarrow being thin

RCA - Initial Lattice building

At the beginning, only the object-attribute contexts are used to build the foundation of the concept lattice family



RCA - Introducing relations as relational attributes

Given an object-object context $R_j = (O_k, O_l, I_j)$,

There are different possible schemas between an object of domain O_k and concepts formed on O_l .


E. g.

- ▶ **Existential**: an object is linked (by R_j) to at least one object of the extent of a concept
- ▶ **Universal**: an object is linked (by R_j) only to objects of the extent of a concept

\exists and \forall are **scaling operators**

RCA - Existential relational attributes

margherita has one topping in Concept_10 extent: **mozza**.
It has other links to other concept extents.





\exists has-topping.Concept_10 is assigned to **margherita**

RCA - Relational extension


Scaled relations with domain O_i are concatenated to K_i , the object-attribute context on O_i

Pizza	thin	thick	calzone		has-topping. Concept_7	has-topping. Concept_5	has-topping. Concept_6	has-topping. Concept_8	has-topping. Concept_9	has-topping. Concept_10	has-topping. Concept_11	has-topping. Concept_12
okonomi			x									
alberginia		x		has-topping	\exists has-topping. Concept_7	\exists has-topping. Concept_5	\exists has-topping. Concept_6	\exists has-topping. Concept_8	\exists has-topping. Concept_9	\exists has-topping. Concept_10	\exists has-topping. Concept_11	\exists has-topping. Concept_12
margherita	x			okonomi		x	x					x
languedoc	x			alberginia		x	x					x
four-cheeses	x			margherita		x	x			x		x
three-cheeses	x			languedoc		x	x			x		x
frutti-di-mare	x			four-cheeses		x				x		
quebec		x		three-cheeses		x				x		
regina	x			frutti-di-mare		x	x		x	x		x
hawai		x		quebec		x	x	x		x	x	
lorraine	x			regina		x	x	x		x		
kebab			x	hawai		x	x	x		x		
				lorraine		x	x	x		x		
				kebab		x	x	x		x		

Relational Concept Family / exists



Relational Concept Family / exists




Concept_21: pizzas with at least one topping in dairy

Concept_18: pizzas with at least one topping in meat

have at least one meat topping \Rightarrow have at least one dairy topping

RCA - Universal relational attributes

three-cheese has topping in and only in **Concept_10** extent.



$\forall E$ has-topping. **Concept_10** is assigned to **three-cheese**



RCA - Relational extension

Scaled relations with domain O_i are concatenated to K_i , the object-attribute context on O_i


Pizza	thin	thick	calzone
okonomi			x
alberginia		x	
margherita	x		
languedoc	x		
four-cheeses	x		
three-cheeses	x		
frutti-di-mare	x		
quebec		x	
regina	x		
hawai		x	
lorraine	x		
kebab			x

	$\forall \exists$ has-topping. Concept_7	$\forall \exists$ has-topping. Concept_5	$\forall \exists$ has-topping. Concept_6	$\forall \exists \exists \exists$ has-topping. Concept_8	$\forall \exists$ has-topping. Concept_9	$\forall \exists \exists$ has-topping. Concept_10	$\forall \exists \exists \exists$ has-topping. Concept_11	$\forall \exists \exists$ has-topping. Concept_12
has-topping								
okonomi		x						
alberginia		x						
margherita		x						
languedoc		x						
four-cheeses		x				x		
three-cheeses		x				x		
frutti-di-mare		x						
quebec		x						
regina		x						
hawai		x						
lorraine		x						
kebab		x						

Relational Concept Family / forall



Relational Concept Family / forall




Concept_13: pizzas with only dairy topping

Concept_1: thin pizzas


have only dairy topping \Rightarrow thin

General Entity-Relationship diagram may have circuits




\exists prefers $\forall \exists$ has-topping $\forall \exists$ has-category $\forall \exists$ is-produced-by

RCA schema



Credit X. Dolques

Interconnected lattices



Analysis of pizza data - object-attribute contexts

Pizza	thin	thick	calzone
forest		×	
occitane			×
three-cheese	×		
four-cheese	×		
lorraine	×		
arctic		×	

People	organic-farmer	conventional-farmer
Amedeo	×	
Amine	×	
Cyril		×
Marianne	×	
Petko		×

Ingredient
tomato-sauce
cream
onion
bacon
salmon
soy-cream
mozza
goat-cheese
emmental
fourme-ambert
eggplant
mushroom

Category	mediterranean	vegan	vegetarian
fruit-vegetable	×	×	×
meat			
fish	×		
dairy	×		×

Analysis of pizza data - object-object contexts

prefers	forest	occitane	three-cheese	four-cheese	lorraine	arctic
Amedeo	×					
Amine		×				
Cyril				×	×	
Marianne			×			×
Petko						×


has-topping	tomato-sauce	cream	onion	bacon	salmon	soy-cream	mozza	goat-cheese	emmental	fourme-ambert	eggplant	mushroom
forest						×						×
occitane	×		×								×	
three-cheese	×						×	×	×			
four-cheese	×	×					×	×	×	×		
lorraine		×	×	×			×					
arctic	×	×			×		×					

Analysis of pizza data - object-object contexts

is-produced-by	Amedeo	Amine	Cyril	Marianne	Petko
tomato-sauce	×	×			
cream			×		
onion	×				
bacon			×		
salmon				×	×
soy-cream		×			
mozza				×	×
goat-cheese					×
emmental				×	×
fourme-ambert				×	×
eggplant		×			
mushroom	×				


has-category	fruit-vegetable	meat	fish	dairy
tomato-sauce	×			
cream				×
onion	×			
bacon		×		
salmon			×	
soy-cream	×			
mozza				×
goat-cheese				×
emmental				×
fourme-ambert				×
eggplant	×			
mushroom	×			

Concept lattice family




\exists prefers $\forall \exists$ has-topping $\forall \exists$ has-category $\forall \exists$ is-produced-by

Concept lattice family




Step 0

Concept lattice family




Step 1

Concept lattice family




Step 2

Concept lattice family




Step 3

Concept lattice family



Step 4

Concept lattice family



- ▶ People: $\exists \text{prefers. Concept_28} \Rightarrow$ organic farmer
- ▶ Ingredient: $\forall \exists \text{has-category. Concept_12} \Leftrightarrow \forall \exists \text{is-produced-by. Concept_6}$ (organic farmers)
- ▶ Amedeo/Amine prefer at least one pizza with only vegan topping ingredients and produced only by organic farmers

Applications to Knowledge Representation and Data Mining

- ▶ Ontology construction (R. Bendaoud, M. Rouane Hacene, Y. Toussaint, B. Delecroix, A. Napoli)
- ▶ Ontology restructuring (M. Rouane-Hacene, R. Nkambou and P. Valtchev)
- ▶ Discovering hidden user profiles in a semantic actors-activities network (Z. Azmeh, I. Mirbel)

FRESQUEAU project (ANR11_MONU14)

Joint work with: A. Braud, X. Dolques, C. Grac, F. Le Ber, C. Nica

<http://engees-fresqueau.unistra.fr>

- ▶ Develop new methods to study, compare and exploit the whole set of available parameters describing the state of watercourses
- ▶ Extraction of implication rules (with premise of size 1)
Presence of taxons of size from 0 to 2 cm and with a lifetime of 1 month implies presence of SO4
- ▶ RCA-AOC
- ▶ Connection with propositionnalization approach
- ▶ Ongoing work on temporal RCA

Reengineering of existing software, by building new software artefacts

- ▶ UML class diagram refactoring (M. Dao, M. Huchard, M. Rouane Hacene, C. Roume, P. Valtchev, G. Arévalo, J.-R. Falleri, C. Nebut)
- ▶ UML Use case diagram refactoring (X. Dolques, M. Huchard, C. Nebut, P. Reitz)
- ▶ Blob design defect correction (N. Moha, M. Rouane Hacene, P. Valtchev, Y.-G. Guéhéneuc)
- ▶ Extracting architectures in object-oriented software (A.-E. El Hamdouni, A. Seriai, M. Huchard)

Learning from model transformation examples, and inferring transformation rules

- ▶ Learning model Transformation patterns in MDE (H. Saada, X. Dolques, M. Huchard, C. Nebut, H. A. Sahraoui)

Classification of software artefacts

- ▶ Classification of web services (Z. Azmeh, M. Driss, F. Hamoui, M. Huchard, N. Moha, C. Tibermacine)

Software analysis

- ▶ Analysis of the evolution of class diagrams (A. Osman-Guédi, A. Miralles, B. Amar, M. Huchard, T. Libourel and C. Nebut)

Conclusion

RCA: an opportunity for analyzing more deeply dataset composed of objects and relations

- ▶ an iterative method to produce interconnected classifications
- ▶ converges after a number of iterations that depends on the structure
- ▶ a variety of scaling operators
- ▶ reduced structures can be used instead of lattices: AOC-posets, iceberg lattices
- ▶ can be mixed with other FCA extension (to numerical data for example)

Ongoing work / Perspectives

- ▶ A querying mechanism and navigation tools
- ▶ Compare systematically AOC-poset, iceberg lattices and concept lattices in the applications
- ▶ Exploration-based methodology (method convergence)